

Vgel chopp



VL

VL



0VL - 1VL - 2VL - 6VL



3VL - 4VL - 5VL



9VL - 10VL

MODELO	VIAS	CAPACIDADE (BTU/h)	L x A x P (mm)	ENTRADA (°C)	SAÍDA (°C)	VAZÃO (L/h)	POTÊNCIA (W)	VOLTAGEM (V)
0VL	1	4.400	390 x 450 x 600	24	1	45	630	110 / 220 - 60 Hz
1VL	1	5.000	390 x 450 x 600	24	1	55	1150	110 / 220 - 60 Hz
2VL	1	7.000	420 x 465 x 690	24	1	80	1520	110 / 220 - 60 Hz
3VL	2	5.000	420 x 465 x 690	24	1	55	1150	110 / 220 - 60 Hz
4VL	2	7.000	420 x 465 x 690	24	1	80	1520	110 / 220 - 60 Hz
5VL	2	4.400	390 x 450 x 600	24	1	45	630	110 / 220 - 60 Hz
6VL	1	3.000	390 x 450 x 600	24	1	30	460	110 / 220 - 60 Hz
9VL	3	5.000	420 x 465 x 690	24	1	55	1150	110 / 220 - 60 Hz
10VL	3	7.000	420 x 465 x 690	24	1	80	1520	110 / 220 - 60 Hz